

Technical specification bucket

JET 86 P

Jokey Euro Tainer Profi



+/- 1 mm

+/- 5 %

dimensions

D1: 270,0 mm


D2: 250,5 mm

D3: 226,0 mm

H:* 221,0 mm

*Height without lid

plastic handle



volume/weight:

•	

weight group:

basic data	volume to rim:	9,50 I	handle types		tolerances
	weight:	240,0 g	metal handle	32,0 g	dimensions:

belt handle
no handle
body grip

13,0 g

roller grips

 decoration
 Digital
 IML
 offset

 height:
 150,0 mm
 193,2 mm
 150,0 mm

 width:
 737,0 mm
 750,9 mm
 720,0 mm

 median breadth:
 737,0 mm

Medium

LidDET 267 PFDET 267 PDET 267 PRstandardsealing lidshaker lidstacking height two fi 427,0 mm451,0 mm427,0 mmeach further:206,0 mm222,0 mm206,0 mm

logistic Max. compression for standard lid at 20°C on the lowest pail: 45,00 kg


pieces per pallet

Bucket 600 pallet height 2,20 m

layer quantities: 13

EUP (Europallet)

80 cm (31,5") x 120 cm (47,24")



material





QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 09.03.2015 rev. 2.0



Technical specification lid **DET 267 P**



JET 103 PC

dimensions

D1: 265,0 mm H: 16,0 mm

basic data displaced volume:: 0,70 I tolerances

> weight: 60,0 g dimensions: +/- 1 mm weight group: Medium volume/weight: +/- 5 %

decoration IML offset

Diameter 232,0 mm 212,0 mm

JET2K 267 P JET 70 P JET 86 P JET 103 P Bucket JET 71 P



pieces per pallet






EUP (Europallet)

80 cm (31,5") x 120 cm (47,24") Lid 3600 pallet height 2,20 m

layer quantities: 13



QM / certificates

material

You can download our current certificates on www.jokey.com.

Date: 09.03.2015 rev. 2.0

misc.

logistic

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved

Please find further Information at www.jokey.com or via email info@jokey.com



Technical specification lid **FDET 267 P**



dimensions

D1: 263,5 mm H: 21,5 mm

basic data displaced volume:: 0,001 tolerances

> weight: 55,0 g dimensions: +/- 1 mm weight group: Medium volume/weight: +/- 5 %

decoration IML offset

Diameter 232,0 mm 0,0 mm

JET 70 P JET 71 P JET 103 P Bucket JET 86 P







JET 103 PC



Date: 19.09.2016 rev. 2.1

JCL 107

logistic

pieces per pallet

Lid 2400 pallet height 2,20 m

layer quantities: 13

EUP (Europallet)

80 cm (31,5") x 120 cm (47,24")

material



You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved

Please find further Information at www.jokey.com or via email info@jokey.com



JET 70 P

Technical specification lid **DET 267 PR**



dimensions

D1: 265,0 mm H: 15,0 mm

basic data displaced volume:: 0,70 I tolerances

> 65,0 g dimensions: +/- 1 mm weight: weight group: Medium volume/weight: +/- 5 %

decoration IML offset

Diameter 0,0 mm 0,0 mm

JET 71 P

JET 86 P



JCL 107



Date: 09.03.2015 rev. 2.0

JET 107 P

logistic

Bucket


pieces per pallet

1200 Lid pallet height 2,20 m

layer quantities: 13

EUP (Europallet)

80 cm (31,5") x 120 cm (47,24")



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com