



# Technical specification bucket



## JETO 110 P

Jokey Euro Tainer oval Profi

### dimensions


D1: 345,0 x 265,0 mm

D2: 332,0 x 253,0 mm

D3: 304,0 x 224,0 mm

H:\* 217,0 mm

\*Height without lid




basic data	volume to rim:	12,30 l	handle types	metal handle	33,0 g	tolerances	dimensions:	+/- 1 mm
	weight:	310,0 g	plastic handle	20,0 g		volume/weight:	+/- 5 %	
	weight group:	Medium	belt handle	-				
			no handle	-				
			body grip	-				
			roller grips	3,0 g				

decoration	Digital	IML	offset
height:	150,0 mm	187,1 mm	150,0 mm
width:	865,0 mm	875,7 mm	850,0 mm
median breadth:			865,0 mm

Lid	DETO 125 P	DETO 125 PR
	standard	shaker lid
stacking height two fi	418,0 mm	419,0 mm
each further:	200,0 mm	200,0 mm

logistic	Max. compression for standard lid at 20°C on the lowest pail: 48,00 kg
<b>pieces per pallet</b>	<b>EUP (Europallet)</b>
Bucket	500
pallet height	2,20 m
layer quantities: 10	80 cm (31,5'') x 120 cm (47,24'')



### material



### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



# Technical specification lid DETO 125 P



## dimensions

D1: 343,3 x 263,3 mm  
H: 19,1 mm

## basic data

displaced volume:: 1,00 l  
weight: 94,0 g  
weight group: Medium

## tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

## decoration

height:  
width:

## IML

0,0 mm  
0,0 mm

## offset

170,0 mm  
250,0 mm

## Bucket

JETO 110 P



JETO 125 P




## logistic

### pieces per pallet

Lid 1800  
pallet height 2,20 m  
layer quantities: 10

### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



## material



### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

## misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



# Technical specification lid DETO 125 PR



## dimensions

D1: 342,9 x 262,9 mm  
H: 19,0 mm

## basic data

displaced volume:: 1,00 l  
weight: 99,0 g  
weight group: Medium

## tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

## decoration

height:  
width:

## IML

0,0 mm  
0,0 mm

## offset

170,0 mm  
250,0 mm

## Bucket

JETO 110 P



JETO 125 P




## logistic

### pieces per pallet

Lid 1800  
pallet height 2,20 m  
layer quantities: 10

### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



## material



### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

## misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 27.10.2016 rev. 2.1