



# Technical specification bucket




## JET 103 P

Jokey Euro Tainer Profi

### dimensions

D1: 270,0 mm  
D2: 250,5 mm  
D3: 226,0 mm  
H:\* 254,0 mm

\*Height without lid




basic data	volume to rim:	11,30 l	handle types	metal handle	32,0 g	tolerances	dimensions:	+/- 1 mm
	weight:	260,0 g	plastic handle		13,0 g	volume/weight:		+/- 5 %
	weight group:	Medium	belt handle		-			
			no handle		-			
			body grip		-			
			roller grips		-			

decoration	Digital	IML	offset
height:	185,0 mm	230,2 mm	185,0 mm
width:	750,0 mm	753,7 mm	735,0 mm
median breadth:			750,0 mm

Lid	DET 267 P	FDET 267 P	DET 267 PR
	standard	sealing lid	shaker lid
stacking height two fi	495,0 mm	517,0 mm	495,0 mm
each further:	241,0 mm	255,0 mm	241,0 mm

logistic	Max. compression for standard lid at 20°C on the lowest pail: 36,00 kg	EUP (Europallet)	material
pieces per pallet		80 cm (31,5'') x 120 cm (47,24'')	PP
Bucket	600		
pallet height	2,20 m		
layer quantities: 13			



### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



# Technical specification lid DET 267 P



## dimensions

D1: 265,0 mm  
H: 16,0 mm

## basic data

displaced volume:: 0,70 l  
weight: 60,0 g  
weight group: Medium

## tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

## decoration

Diameter

## IML

232,0 mm

## offset

212,0 mm

## Bucket




## logistic

### pieces per pallet

Lid 3600  
pallet height 2,20 m  
layer quantities: 13

### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



## material



### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

## misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 09.03.2015 rev. 2.0



# Technical specification lid

## FDET 267 P



### dimensions

D1: 263,5 mm  
H: 21,5 mm

### basic data

displaced volume:: 0,00 l  
weight: 55,0 g  
weight group: Medium

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

Diameter

### IML

232,0 mm

### offset

0,0 mm

### Bucket



### logistic

#### pieces per pallet

Lid 2400  
pallet height 2,20 m  
layer quantities: 13

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')

### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 19.09.2016 rev. 2.1



# Technical specification lid

## DET 267 PR



### dimensions

D1: 265,0 mm  
H: 15,0 mm

### basic data

displaced volume:: 0,70 l  
weight: 65,0 g  
weight group: Medium

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

Diameter

### IML

0,0 mm

### offset

0,0 mm

### Bucket

JET 70 P



JET 71 P



JET 86 P



JET 103 P



JCL 107



JET 107 P




### logistic

#### pieces per pallet

Lid 1200  
pallet height 2,20 m  
layer quantities: 13

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 09.03.2015 rev. 2.0