



Technical specification bucket

JET 103 PC

Jokey Euro Tainer Profi Cylindrical



dimensions


D1: 270,0 mm

D2: 250,5 mm

D3: 228,0 mm


H:* 254,0 mm

*Height without lid



basic data	volume to rim:	11,30 l	handle types	metal handle	-	tolerances	dimensions:	+/- 1 mm
	weight:	248,0 g		plastic handle	10,0 g		volume/weight:	+/- 5 %
	weight group:	Light		belt handle	-			
			no handle	-				
			body grip	-				
			roller grips	-				
decoration	Digital		IML			offset		
height:	0,0 mm		221,0 mm			0,0 mm		
width:	0,0 mm		757,2 mm			0,0 mm		
median breadth:						0,0 mm		
Lid	DET 267 P	FDET 267 P						
	standard	sealing lid						
stacking height two fi	495,0 mm	517,0 mm						
each further:	240,0 mm	255,0 mm						

logistic	Max. compression for standard lid at 20°C on the lowest pail: 36,00 kg	
	pieces per pallet	EUP (Europallet)
	Bucket	600
	pallet height	2,20 m
	layer quantities: 13	



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 18.09.2017 rev. 2.5



Technical specification lid DET 267 P



dimensions

D1: 265,0 mm
H: 16,0 mm

basic data

displaced volume:: 0,70 l
weight: 60,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

232,0 mm

offset

212,0 mm

Bucket




logistic

pieces per pallet

Lid 3600
pallet height 2,20 m
layer quantities: 13

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 09.03.2015 rev. 2.0



Technical specification lid

FDET 267 P



dimensions

D1: 263,5 mm
H: 21,5 mm

basic data

displaced volume:: 0,00 l
weight: 55,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

232,0 mm

offset

0,0 mm

Bucket



logistic

pieces per pallet

Lid 2400
pallet height 2,20 m
layer quantities: 13

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')

material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 19.09.2016 rev. 2.1