



Technical specification bucket

JET 110 PC


Jokey Euro Tainer Profi Cylindrical



dimensions

D1: 294,0 mm
D2: 277,0 mm
D3: 257,5 mm
H:* 222,0 mm

*Height without lid



basic data

volume to rim: 12,20 l
weight: 290,0 g
weight group: Medium

handle types

metal handle 39,0 g
plastic handle 11,0 g
belt handle -
no handle -
body grip -
roller grips -

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Digital

height: 0,0 mm
width: 0,0 mm
median breadth:

IML

185,2 mm
846,6 mm

offset

0,0 mm
0,0 mm
0,0 mm

Lid

DET 290 P

standard

stacking height two fi 432,0 mm
each further: 210,0 mm

FDET 290 P

sealing lid

452,0 mm
222,5 mm

FDET 290 P

sealing lid

0,0 mm
0,0 mm

logistic

Max. compression for standard lid at 20°C on the lowest pail: 56,00 kg


pieces per pallet

Bucket 550
pallet height 2,20 m

layer quantities: 11

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 21.04.2016 rev. 2.4



Technical specification lid

DET 290 P



dimensions

D1: 289,0 mm
H: 15,0 mm

basic data

displaced volume:: 0,70 l
weight: 70,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

260,0 mm

offset

230,0 mm

Bucket

JET 110 P



JET 110 PC



JET 125 P



JET 150 P




logistic

pieces per pallet

Lid 2200
pallet height 2,20 m
layer quantities: 11

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 09.03.2015 rev. 2.0



Technical specification lid

FDET 290 P



dimensions

D1: 286,0 mm
H: 21,5 mm

basic data

displaced volume:: 0,00 l
weight: 73,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

0,0 mm

offset

0,0 mm

Bucket

JET 110 P



JET 110 PC



JET 125 P



JET 150 P




logistic

pieces per pallet

Lid 2200
pallet height 2,20 m
layer quantities: 11

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 09.03.2015 rev. 2.0



Technical specification lid

FDET 290 P



dimensions

D1: 286,0 mm
H: 21,5 mm

basic data

displaced volume:: 0,00 l
weight: 70,0 g
weight group: Light

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

0,0 mm

offset

0,0 mm

Bucket

JET 110 P



JET 110 PC



JET 125 P



JET 150 P




logistic

pieces per pallet

Lid 2200
pallet height 2,20 m
layer quantities: 11

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 23.03.2016 rev. 2.0