



Technical specification bucket

JET 125 P


Jokey Euro Tainer Profi



dimensions


D1: 293,0 mm
D2: 277,0 mm
D3: 253,0 mm
H:* 255,0 mm

*Height without lid



basic data	volume to rim:	13,90 l	handle types	metal handle	39,0 g	tolerances	dimensions:	+/- 1 mm
	weight:	367,0 g		plastic handle	16,0 g		volume/weight:	+/- 5 %
	weight group:	Medium		belt handle	-			
				no handle	-			
			body grip	-				
			roller grips	-				
decoration	Digital		IML			offset		
height:	185,0 mm		225,6 mm			185,0 mm		
width:	825,0 mm		842,2 mm			810,0 mm		
median breadth:						825,0 mm		
Lid	DET 290 P	DET 290 PR	FDET 290 P	DET 290 PR	FDET 290 P			
	standard	shaker lid	sealing lid	shaker lid	sealing lid			
stacking height two f	500,0 mm	500,0 mm	519,0 mm	0,0 mm	0,0 mm			
each further:	244,0 mm	244,0 mm	256,0 mm	0,0 mm	0,0 mm			

logistic	Max. compression for standard lid at 20°C on the lowest pail: 54,00 kg	
	pieces per pallet	EUP (Europallet)
	Bucket	550
	pallet height	2,20 m
	80 cm (31,5'') x 120 cm (47,24'')	
	layer quantities: 11	



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



Technical specification lid

DET 290 P



dimensions

D1: 289,0 mm
H: 15,0 mm

basic data

displaced volume:: 0,70 l
weight: 70,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

260,0 mm

offset

230,0 mm

Bucket

JET 110 P



JET 110 PC



JET 125 P



JET 150 P




logistic

pieces per pallet

Lid 2200
pallet height 2,20 m
layer quantities: 11

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 09.03.2015 rev. 2.0



Technical specification lid DET 290 PR



dimensions

D1: 289,0 mm
H: 15,0 mm

basic data

displaced volume:: 0,70 l
weight: 85,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

260,0 mm

offset

230,0 mm

Bucket

JET 110 P



JET 125 P



JET 150 P




logistic

pieces per pallet

Lid 2200
pallet height 2,20 m
layer quantities: 11

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 09.03.2015 rev. 2.0



Technical specification lid

FDET 290 P



dimensions

D1: 286,0 mm
H: 21,5 mm

basic data

displaced volume:: 0,00 l
weight: 73,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

0,0 mm

offset

0,0 mm

Bucket

JET 110 P



JET 110 PC



JET 125 P



JET 150 P




logistic

pieces per pallet

Lid 2200
pallet height 2,20 m
layer quantities: 11

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 09.03.2015 rev. 2.0



Technical specification lid

DET 290 PR



dimensions

D1: 289,0 mm
H: 15,0 mm

basic data

displaced volume:: 0,70 l
weight: 80,0 g
weight group: Light

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

260,0 mm

offset

230,0 mm

Bucket

JET 110 P



JET 125 P



JET 150 P




logistic

pieces per pallet

Lid 2200
pallet height 2,20 m
layer quantities: 11

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 09.03.2015 rev. 2.0



Technical specification lid

FDET 290 P



dimensions

D1: 286,0 mm
H: 21,5 mm

basic data

displaced volume:: 0,00 l
weight: 70,0 g
weight group: Light

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

0,0 mm

offset

0,0 mm

Bucket

JET 110 P



JET 110 PC



JET 125 P



JET 150 P




logistic

pieces per pallet

Lid 2200
pallet height 2,20 m
layer quantities: 11

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 23.03.2016 rev. 2.0