



Technical specification bucket

JET 200 P

Jokey Euro Tainer Profi



dimensions


D1: 326,0 mm

D2: 311,0 mm

D3: 282,0 mm

H:* 312,5 mm

*Height without lid



basic data

volume to rim: 21,20 l
weight: 560,0 g
weight group: Medium

handle types

metal handle 57,0 g
plastic handle 28,0 g
belt handle -
no handle -
body grip -
roller grips 3,0 g

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Digital

height: 0,0 mm
width: 0,0 mm
median breadth:

IML

274,2 mm
937,7 mm

offset

230,0 mm
930,0 mm
945,0 mm

Lid

| | DET 325 P | DET 325 PR | DET 325 P | FDET 325 P |
|-----------------------|-----------|------------|-----------|-------------|
| | standard | shaker lid | standard | sealing lid |
| stacking height two f | 614,0 mm | 614,0 mm | 0,0 mm | 0,0 mm |
| each further: | 301,0 mm | 301,0 mm | 0,0 mm | 0,0 mm |

logistic

Max. compression for standard lid at 20°C on the lowest pail: 65,00 kg


pieces per pallet

Bucket 320
pallet height 2,20 m

layer quantities: 8

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 27.10.2016 rev. 2.1



Technical specification lid DET 325 P



dimensions

D1: 325,3 mm
H: 14,4 mm

basic data

displaced volume:: 1,00 l
weight: 100,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

279,0 mm

offset

250,0 mm

Bucket

JET2K 325 P



JET2K 325 Pt

JET 160 P



JET 180 P



JET 200 P



JET 201 P



JET 210 P




logistic

pieces per pallet

Lid 1920
pallet height 2,20 m
layer quantities: 8

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 09.03.2015 rev. 2.0



Technical specification lid

DET 325 PR



dimensions

D1: 325,0 mm
H: 16,0 mm

basic data

displaced volume:: 1,20 l
weight: 120,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

279,0 mm

offset

250,0 mm

Bucket

JET2K 325 P



JET 160 P



JET 180 P



JET 200 P



JET 201 P



JET 210 P




logistic

pieces per pallet

Lid 960
pallet height 2,20 m
layer quantities: 8

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 09.03.2015 rev. 2.0



Technical specification lid

DET 325 P



dimensions

D1: 325,3 mm
H: 14,4 mm

basic data

displaced volume:: 1,00 l
weight: 115,0 g
weight group: Heavy

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

279,0 mm

offset

250,0 mm

Bucket

JET2K 325 P



JET2K 325 Pt

JET 160 P



JET 180 P



JET 200 P



JET 201 P



JET 210 P




logistic

pieces per pallet

Lid 960
pallet height 2,20 m
layer quantities: 8

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 09.03.2015 rev. 2.0



Technical specification lid

FDET 325 P



dimensions

D1: 325,0 mm
H: 23,5 mm

basic data

displaced volume:: 0,00 l
weight: 118,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

279,0 mm

offset

250,0 mm

Bucket

JET 160 P



JET 180 P



JET 200 P



JET 201 P



JET 210 P




logistic

pieces per pallet

Lid 720
pallet height 1,20 m
layer quantities: 8

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 27.04.2016 rev. 2.1