



# Technical specification bucket


## JET 260 P

Jokey Euro Tainer Profi



### dimensions

D1: 380,0 mm  
 D2: 358,0 mm  
 D3: 320,0 mm  
 H:\* 325,0 mm  
 \*Height without lid



### basic data

volume to rim: 29,10 l  
 weight: 645,0 g  
 weight group: Medium

### handle types

metal handle 80,0 g  
 plastic handle -  
 belt handle -  
 no handle +  
 body grip +  
 roller grips 3,0 g

### tolerances

dimensions: +/- 1 mm  
 volume/weight: +/- 5 %

### decoration

#### Digital

height: 220,0 mm  
 width: 1080,0 mm  
 median breadth:

#### IML

0,0 mm  
 0,0 mm

#### offset

240,0 mm  
 945,0 mm  
 1080,0 mm

### Lid

	DET 380 P	FDET 380 P	DET 380 Pt	DET 380 P	DET 380 P
	standard	sealing lid	recessed lid	standard	standard
stacking height two f	637,0 mm	656,9 mm	627,2 mm	0,0 mm	0,0 mm
each further:	311,0 mm	305,0 mm	301,2 mm	0,0 mm	0,0 mm

### logistic

Max. compression for standard lid at 20°C on the lowest pail: 65,00 kg


#### pieces per pallet

Bucket 240  
 pallet height 2,20 m

layer quantities: 6

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



# Technical specification lid DET 380 P



### dimensions

D1: 374,7 mm  
H: 15,7 mm

### basic data

displaced volume:: 1,50 l  
weight: 140,0 g  
weight group: Medium

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

Diameter

### IML

279,0 mm

### offset

270,0 mm

### Bucket

JET2K 380 P



JETK 160



JETK 180



JET 230 P



JET 260 P



JET 300 P



JET 320 P




### logistic

#### pieces per pallet

Lid 1296  
pallet height 2,20 m  
layer quantities: 6

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 18.08.2017 rev. 2.1



# Technical specification lid

## FDET 380 P



### dimensions

D1: 376,0 mm  
H: 27,2 mm

### basic data

displaced volume:: 0,00 l  
weight: 178,0 g  
weight group: Medium

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

Diameter

### IML

0,0 mm

### offset

0,0 mm

### Bucket

JET 260 P



JET 300 P



JET 320 P



### logistic

#### pieces per pallet

Lid 1296  
pallet height 2,20 m  
layer quantities: 6

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')

### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 09.03.2015 rev. 2.0



# Technical specification lid

## DET 380 Pt



### dimensions

D1: 376,0 mm  
H: 26,2 mm

### basic data

displaced volume:: 2,40 l  
weight: 195,0 g  
weight group: Heavy

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

Diameter

### IML

0,0 mm

### offset

0,0 mm

### Bucket

JET 260 P



JET 300 P



JET 320 P




### logistic

#### pieces per pallet

Lid 1296  
pallet height 2,20 m  
layer quantities: 6

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 09.03.2015 rev. 2.0



# Technical specification lid

## DET 380 P



### dimensions

D1: 374,7 mm  
H: 15,7 mm

### basic data

displaced volume:: 1,50 l  
weight: 160,0 g  
weight group: Heavy

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

Diameter

### IML

279,0 mm

### offset

270,0 mm

### Bucket

JET2K 380 P



JETK 160



JETK 180



JET 230 P



JET 260 P



JET 300 P



JET 320 P




### logistic

#### pieces per pallet

Lid 1296  
pallet height 2,20 m  
layer quantities: 6

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 30.07.2015 rev. 2.1



# Technical specification lid

## DET 380 P



### dimensions

D1: 374,7 mm  
H: 15,7 mm

### basic data

displaced volume:: 1,50 l  
weight: 130,0 g  
weight group: Light

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

Diameter

### IML

279,0 mm

### offset

270,0 mm

### Bucket

JET2K 380 P



JETK 160



JETK 180



JET 230 P



JET 260 P



JET 300 P



JET 320 P




### logistic

#### pieces per pallet

Lid 1296  
pallet height 2,20 m  
layer quantities: 6

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 23.10.2015 rev. 2.1