



# Technical specification bucket

## JET 38 P


Jokey Euro Tainer Profi



### dimensions

D1: 201,5 mm  
D2: 184,0 mm  
D3: 166,0 mm  
H:\* 176,0 mm

\*Height without lid



basic data	volume to rim:	4,20 l	handle types	metal handle	15,0 g	tolerances	dimensions:	+/- 1 mm
	weight:	115,0 g	plastic handle		5,0 g	volume/weight:		+/- 5 %
	weight group:	Medium	belt handle		-			
			no handle		-			
			body grip		-			
			roller grips		-			

decoration	Digital	IML	offset
height:	120,0 mm	156,2 mm	120,0 mm
width:	550,0 mm	554,6 mm	540,0 mm
median breadth:			550,0 mm

Lid	DET 200 P	DET 200 PR	FDET 200 P	FDET 200 P
	standard	shaker lid	sealing lid	sealing lid
stacking height two fi	343,0 mm	347,3 mm	359,0 mm	359,0 mm
each further:	167,0 mm	170,3 mm	176,5 mm	176,5 mm

**logistic** Max. compression for standard lid at 20°C on the lowest pail: 23,00 kg


### pieces per pallet

Bucket 760  
pallet height 1,20 m

layer quantities: 24

### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 02.05.2017 rev. 2.5



# Technical specification lid

## DET 200 P



### dimensions

D1: 197,0 mm  
H: 12,0 mm

### basic data

displaced volume:: 0,30 l  
weight: 24,0 g  
weight group: Medium

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

Diameter

### IML

175,0 mm

### offset

145,0 mm

### Bucket

JET 10 P



JET 22 P



JET 25 P



JET 30 P



JET 34 P



JET 34 PC



JET 38 P



JET 38 PC




### logistic

#### pieces per pallet

Lid 4560  
pallet height 1,20 m  
layer quantities: 24

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 09.03.2015 rev. 2.0



# Technical specification lid

## DET 200 PR



### dimensions

D1: 197,0 mm  
H: 11,8 mm

### basic data

displaced volume:: 0,30 l  
weight: 25,0 g  
weight group: Medium

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

Diameter

### IML

175,0 mm

### offset

145,0 mm

### Bucket

JET 22 P



JET 30 P



JET 34 PC



JET 38 P



JET 38 PC




### logistic

#### pieces per pallet

Lid 4560  
pallet height 1,20 m  
layer quantities: 24

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 09.03.2015 rev. 2.0



# Technical specification lid

## FDET 200 P



### dimensions

D1: 196,0 mm  
H: 17,2 mm

### basic data

displaced volume:: 0,00 l  
weight: 28,0 g  
weight group: Medium

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

Diameter

### IML

175,0 mm

### offset

0,0 mm

### Bucket

JET 22 P



JET 25 P



JET 30 P



JET 34 P



JET 34 PC



JET 38 P



JET 38 PC




### logistic

#### pieces per pallet

Lid 4560  
pallet height 1,20 m  
layer quantities: 24

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 09.03.2015 rev. 2.0



# Technical specification lid

## FDET 200 P



### dimensions

D1: 196,0 mm  
H: 17,2 mm

### basic data

displaced volume:: 0,00 l  
weight: 25,0 g  
weight group: Light

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

Diameter

### IML

175,0 mm

### offset

0,0 mm

### Bucket

JET 22 P



JET 25 P



JET 30 P



JET 34 P



JET 34 PC



JET 38 P



JET 38 PC




### logistic

#### pieces per pallet

Lid 4560  
pallet height 1,20 m  
layer quantities: 24

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 09.10.2017 rev. 2.1