




Technical specification bucket JET 55 PC



Jokey Euro Tainer Profi Cylindrical

dimensions

D1: 227,0 mm
D2: 210,0 mm
D3: 195,5 mm
H:* 187,5 mm
*Height without lid



basic data

volume to rim: 6,04 l
weight: 121,0 g
weight group: Light

handle types

metal handle -
plastic handle 9,0 g
belt handle -
no handle -
body grip -
roller grips -

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Digital

height: 0,0 mm
width: 0,0 mm
median breadth:

IML

167,0 mm
646,0 mm

offset

0,0 mm
0,0 mm
0,0 mm

Lid

	DET 225 P	DET 56 P	FDET 225 P
	standard	standard	sealing lid
stacking height two fi	365,9 mm	363,4 mm	384,1 mm
each further:	177,4 mm	174,9 mm	188,6 mm

logistic

Max. compression for standard lid at 20°C on the lowest pail: 18,50 kg


pieces per pallet

Bucket 1080
pallet height 2,20 m

layer quantities: 18

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 01.02.2018 rev. 2.2



Technical specification lid DET 225 P



dimensions

D1: 223,0 mm
H: 12,0 mm

basic data

displaced volume:: 0,30 l
weight: 35,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

194,0 mm

offset

182,0 mm

Bucket




logistic

pieces per pallet

Lid 5400
pallet height 2,20 m
layer quantities: 18

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 25.04.2017 rev. 2.2



Technical specification lid DET 56 P



dimensions

D1: 223,0 mm
H: 12,0 mm

basic data

displaced volume:: 0,35 l
weight: 35,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

0,0 mm

offset

0,0 mm

Bucket

JET 53 PC



JET 56 P



JET 55 PC




logistic

pieces per pallet

Lid 5400
pallet height 2,20 m
layer quantities: 18

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 09.03.2015 rev. 2.0



Technical specification lid

FDET 225 P



dimensions

D1: 222,0 mm
H: 19,0 mm

basic data

displaced volume:: 0,00 l
weight: 32,0 g
weight group: Light

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

0,0 mm

offset

0,0 mm

Bucket

JSP 1026



JET 35 P



JSL 40



JET 44 P



JET 50 P



JSL 53



JET 53 P



JET 53 PC



JET 56 P



JET 55 PC



JET 62 P




logistic

pieces per pallet

Lid 4800
pallet height 2,20 m
layer quantities: 18

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 26.08.2016 rev. 2.1