



Technical specification bucket



JETO 170 P

Jokey Euro Tainer oval Profi

dimensions


D1: 391,0 x 301,0 mm

D2: 376,0 x 286,0 mm

D3: 353,0 x 263,0 mm

H:* 241,0 mm

*Height without lid



basic data	volume to rim:	18,70 l	handle types	metal handle	46,0 g	tolerances	dimensions:	+/- 1 mm
	weight:	480,0 g		plastic handle	-		volume/weight:	+/- 5 %
	weight group:	Medium		belt handle	-			
			no handle	-				
			body grip	-				
			roller grips	3,0 g				
decoration	Digital		IML			offset		
height:	175,0 mm		0,0 mm			175,0 mm		
width:	1010,0 mm		0,0 mm			945,0 mm		
median breadth:						1010,0 mm		
Lid	DETO 180 P	DETO 180 PR						
	standard	shaker lid						
stacking height two fi	463,0 mm	466,0 mm						
each further:	221,0 mm	224,0 mm						

logistic	Max. compression for standard lid at 20°C on the lowest pail: 72,00 kg	
	pieces per pallet	EUP (Europallet)
	Bucket 400	80 cm (31,5'') x 120 cm (47,24'')
	pallet height 2,20 m	
layer quantities: 8		

material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



Technical specification lid

DETO 180 P



dimensions

D1: 389,0 x 299,0 mm
H: 22,2 mm

basic data

displaced volume:: 1,50 l
weight: 130,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

height:
width:

IML

266,0 mm
189,0 mm

offset

225,0 mm
300,0 mm

Bucket

JETO 150 P



JETO 170 P



JETO 180 P




logistic

pieces per pallet

Lid 1280
pallet height 2,20 m
layer quantities: 8

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 09.03.2015 rev. 2.0



Technical specification lid

DETO 180 PR



dimensions

D1: 389,0 x 299,0 mm
H: 16,0 mm

basic data

displaced volume:: 1,30 l
weight: 135,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

height:
width:

IML

266,0 mm
189,0 mm

offset

225,0 mm
300,0 mm

Bucket

JETO 150 P



JETO 170 P



JETO 180 P




logistic

pieces per pallet

Lid 1200
pallet height 2,20 m
layer quantities: 8

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 09.03.2015 rev. 2.0