



Technical specification bucket

JETQ 30 P




Jokey Euro Tainer square Profi

dimensions

- D1: 197,2 x 197,2 mm
- D2: 186,0 x 186,0 mm
- D3: 167,0 x 167,0 mm
- H:* 126,1 mm

*Height without lid



basic data

volume to rim: 3,50 l
weight: 95,0 g
weight group: Heavy

handle types

- metal handle -
- plastic handle -
- fitted handle tight 6,0 g
- no handle +
- body grip -
- roller grips -

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Digital

height: 75,0 mm
width: 645,0 mm
median breadth:

IML

103,4 mm
639,5 mm

offset

75,0 mm
100,0 mm
645,0 mm

Lid

DETQ 50 P

FDETQ 50 P

FDETQ 50 PQ

	standard	sealing lid	sealing lid
stacking height two fi	236,0 mm	254,0 mm	254,0 mm
each further:	109,0 mm	127,0 mm	127,0 mm

logistic

Max. compression for standard lid at 20°C on the lowest pail: 20,00 kg


pieces per pallet

Bucket 1920
pallet height 2,20 m

layer quantities: 24

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



Technical specification lid DETQ 50 P



dimensions

D1: 194,8 x 194,8 mm
H: 19,1 mm

basic data

displaced volume:: 0,60 l
weight: 36,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

height:
width:

IML

163,7 mm
163,7 mm

offset

0,0 mm
0,0 mm

Bucket

JETQ 30 P

JETQ 35 P

JETQ 44 P

JETQ 50 P




logistic

pieces per pallet

Lid 2736
pallet height 1,20 m
layer quantities: 24

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



Technical specification lid

FDETQ 50 P



dimensions

D1: 193,0 x 193,0 mm
H: 20,7 mm

basic data

displaced volume:: 0,00 l
weight: 39,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

height:
width:

IML

163,7 mm
163,7 mm

offset

0,0 mm
0,0 mm

Bucket

JETQ 30 P



JETQ 31



JETQ 35 P



JETQ 44 P



JSTQ 50



JETQ 50 P



JETQ 51




logistic

pieces per pallet

Lid 2736
pallet height 1,20 m
layer quantities: 24

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 09.03.2015 rev. 2.0



Technical specification lid

FDETQ 50 PQ



dimensions

D1: 193,0 x 193,0 mm
H: 20,7 mm

basic data

displaced volume:: 0,00 l
weight: 41,0 g
weight group: Medium

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

0,0 mm

offset

0,0 mm

Bucket

JETQ 30 P

JETQ 35 P

JETQ 44 P

JSTQ 50

JETQ 50 P




logistic

pieces per pallet

Lid 3696
pallet height 1,40 m
layer quantities: 24

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.