



# Technical specification bucket

## JETQ 50 P


Jokey Euro Tainer square Profi



### dimensions

- D1: 199,0 x 199,0 mm
- D2: 186,0 x 186,0 mm
- D3: 167,0 x 167,0 mm
- H:\* 201,0 mm

\*Height without lid



### basic data

volume to rim: 6,00 l  
weight: 145,0 g  
weight group: Medium

### handle types

- metal handle -
- plastic handle -
- fitted handle tight 6,0 g
- no handle -
- body grip -
- roller grips -

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

#### Digital

height: 150,0 mm  
width: 635,0 mm  
median breadth:

#### IML

179,8 mm  
649,4 mm

#### offset

150,0 mm  
100,0 mm  
635,0 mm

### Lid

#### DETQ 50 P

#### FDETQ 50 P

#### FDETQ 50 PQ

standard  
stacking height two fi 385,0 mm  
each further: 184,0 mm

sealing lid  
411,0 mm  
201,0 mm

sealing lid  
0,0 mm  
0,0 mm

### logistic

Max. compression for standard lid at 20°C on the lowest pail: 20,00 kg


#### pieces per pallet

Bucket 1920  
pallet height 2,20 m

layer quantities: 24

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



# Technical specification lid DETQ 50 P



## dimensions

D1: 194,8 x 194,8 mm  
H: 19,1 mm

## basic data

displaced volume:: 0,60 l  
weight: 36,0 g  
weight group: Medium

## tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

## decoration

height:  
width:

## IML

163,7 mm  
163,7 mm

## offset

0,0 mm  
0,0 mm

## Bucket

JETQ 30 P

JETQ 35 P

JETQ 44 P

JETQ 50 P




## logistic

### pieces per pallet

Lid 2736  
pallet height 1,20 m  
layer quantities: 24

### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



## material



### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

## misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



# Technical specification lid

## FDETQ 50 P



### dimensions

D1: 193,0 x 193,0 mm  
H: 20,7 mm

### basic data

displaced volume:: 0,00 l  
weight: 39,0 g  
weight group: Medium

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

height:  
width:

### IML

163,7 mm  
163,7 mm

### offset

0,0 mm  
0,0 mm

### Bucket

JETQ 30 P



JETQ 31



JETQ 35 P



JETQ 44 P



JSTQ 50



JETQ 50 P



JETQ 51




### logistic

#### pieces per pallet

Lid 2736  
pallet height 1,20 m  
layer quantities: 24

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



# Technical specification lid

## FDETQ 50 PQ



### dimensions

D1: 193,0 x 193,0 mm  
H: 20,7 mm

### basic data

displaced volume:: 0,00 l  
weight: 41,0 g  
weight group: Medium

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

Diameter

### IML

0,0 mm

### offset

0,0 mm

### Bucket

JETQ 30 P

JETQ 35 P

JETQ 44 P

JSTQ 50

JETQ 50 P




### logistic

#### pieces per pallet

Lid 3696  
pallet height 1,40 m  
layer quantities: 24

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.